


FreeCram



FreeCram

HOME ALL VENDORS DOWNLOAD FREE GUARANTEE FAQs

Pass Your Next Certification Exam Fast!

Select a vendor... Select an test... Your email address [Download Free](#)



Instant Download



365 Days Free Updates



Money Back Guarantee



Security & Privacy

Full refund if you fail the corresponding exam in 60 days after purchasing. And Free get any another product.

We're not the only ones **happy** about FreeCram Practice Material ...

12514+ customers in 100+ countries use FreeCram Test Engine. Meet our customers.

<https://www.freecram.com>

Free Exam/Cram Practice Materials.

Exam : **NS0-175**

Title : Cisco and NetApp FlexPod
Design Specialist

Vendor : Network Appliance

Version : DEMO

NO.1 You are configuring Cisco UCS servers for Fibre Channel SAN boot and want to perform zoning on your Cisco Nexus 5000 series switches.

Which statement is correct in this scenario?

- A. An iSCSI license on the NetApp storage controller is required.
- B. SAN links are required between the Fabric Interconnects and the Nexus 5000 switches.
- C. The corresponding FC ports on your NetApp storage array must be configured in LACP mode.
- D. Fibre Channel zoning on the Nexus series switches is not supported and can only be done on the Fabric Interconnects.

Answer: D

NO.2 You are sizing a FlexPod Virtual Desktop solution for a customer with 500 virtual desktops in a shared Remote Desktop Services (RDS) topology.

In this scenario, which Cisco best practice should you use?

- A. You should avoid placing more than 20 users per physical host
- B. You should avoid changing the virtual host disk queue depth
- C. You should avoid over-committing physical CPU resources for virtual machines
- D. You should avoid multiple vCPUs per individual virtual machine

Answer: C

NO.3 What is the maximum number of power supplies supported in a Cisco UCS 5108 blade server chassis?

- A. 1
- B. 2
- C. 4
- D. 3

Answer: C

NO.4 Which of the following are supported interface types?

- A. 10/100 Ethernet
- B. Gigabit Ethernet, copper
- C. Gigabit Ethernet, fiber
- D. ATM

Answer: A,B,C

NO.5 Cisco UCS Manager supports which three remote authentication methods? (Choose three.)

- A. RADIUS
- B. TACACS+
- C. LDAP
- D. NetBIOS
- E. WINS

Answer: A,C,E

NO.6 For which of the following would the "NTLM Cache" feature normally be used?

- A. Enables the caching and reuse of NTLM challenges in order to reduce the processing load on the domain controller.
- B. Enables NetCache to authenticate users using NTLM.
- C. Enables cached objects retrieved as the result of a successful NTLM exchange to be served to new users without requiring authentication.
- D. Enables NetCache to cache NTLM-authenticated objects.

Answer: A

NO.7 Which of the following TWO statements are FALSE?

- A. The HTTP log file cannot be pushed to a remote HTTPS server at scheduled intervals.
- B. The HTTP log file can be pushed to a remote FTP server in compressed format
- C. The Messages log file cannot be pushed to a remote FTP server in compressed format.
- D. The Messages log file can be pushed to a remote FTP server at scheduled intervals

Answer: A,D

NO.8 The configure "Shared User Hosts" feature under the Appliance Manager's Setup > FTP > Caching Behavior is used to specify: _____ .

- A. a subset of FTP servers that will be accelerated by the NetCache appliance
- B. FTP servers from which fetched objects will be cached and served without a user-specific key requirement in order to increase the caching efficiency
- C. a subset of FTP servers that can be bound to a shared virtual IP address in order to increase overall caching efficiency
- D. a shared IP address that all requesting clients will use to circumvent any authentication or user-specific key requirements on the backend FTP servers

Answer: B

NO.9 An administrator wants to ensure secure authentication while accessing a NetApp ONTAP system.

In this scenario, which two access methods should be used? (Choose two.)

- A. SSH
- B. RSH
- C. HTTPS
- D. HTTP

Answer: A,B

NO.10 Your environment currently has a 12-node NetApp cluster serving iSCSI. You need to add at least four more nodes to serve FC to your environment.

In this scenario, what should you do?

- A. You must create a new cluster with the new storage controllers
- B. You can safely add up to 12 more storage controllers in the current cluster
- C. You can safely add up to 6 more storage controllers in the current cluster
- D. You can safely add up to 4 more storage controllers in the current cluster

Answer: D

NO.11 You are working with a customer on a new FlexPod solution. The customer advises you that they want a single point of contact for support issues.

In this scenario, which two support solutions should you offer the customer? (Choose two.)

- A. Cisco Solution Support
- B. Cisco SmartNet Total Care
- C. NetApp Solution Support for FlexPod
- D. NetApp SupportEdge Expert

Answer: B,C

NO.12 An administrator plans to boot multiple VMware ESXi servers over FCoE within the FlexPod environment.

In this scenario, which UCS feature should be configured to ensure a unique SAN initiator for each host?

- A. UUID pool
- B. WWPN pool
- C. IQN pool
- D. MAC pool

Answer: C

NO.13 One of the below ACLs will OK the requests from Engineering groups to www.netapp.com, which one could it be?

- A. allow group "engineering" and server-domain www.netapp.com
- B. allow groupname "engineering" and server-name matches ".netapp\.com\$"
- C. allow groupname "engineering" and server-name www.netapp.com
- D. allow group "engineering" and server-name www.netapp.com

Answer: D

NO.14 The _____ log only reports Web request data.

- A. Web Server Acceleration
- B. Web Details
- C. Web Access
- D. Messages

Answer: B

NO.15 You want to add a customer's NetApp storage controllers into their Cisco Intersight management portal.

In this scenario, which IP address would you choose to add?

- A. NetApp SVM management IP address
- B. NetApp Virtual Storage Console IP address
- C. NetApp Active IQ Unified Manager IP address
- D. NetApp cluster IP address

Answer: C

NO.16 Your customer has a FlexPod solution with a 2-node switchless ONTAP system, Cisco Nexus 93108 switches, and Cisco UCS B-Series servers. The customer wants to expand to a 4-node ONTAP storage cluster.

Which configuration is valid for expansion?

- A. Add one Nexus 3232C switch for the cluster interconnect.
- B. Add two Nexus 93108 switches for the cluster interconnect.
- C. Add two Nexus 3232C switches for the cluster interconnect.
- D. Use the existing Nexus 93108 switches for the cluster interconnect.

Answer: C

NO.17 For FI 6248 with a GEM module, what is the possible assignment of ports for native Fibre Channel and Ethernet?

- A. Eth ports: 1-21, Fibre Channel ports. 22-48
- B. Eth ports: 1-18, 33-40, Fibre Channel ports. 19-32, 41-48
- C. Eth ports: 1-16, 41-48, Fibre Channel ports. 17-40
- D. Eth ports: 1-21, 33-48, Fibre Channel ports. 22-32

Answer: B

NO.18 State whether the following statement is true or false. All NetApp Services do not include System Administration Services.

- A. True
- B. False

Answer: A

NO.19 Product documentation is available on the appliance and at _____

- A. documentation.netapp.com
- B. www.netapp.com
- C. ftp.netapp.com
- D. now.netapp.com

Answer: D

NO.20 How many cluster interconnect switch(es) are required for a 4-node NetApp cluster?

- A. 6
- B. 2
- C. 1
- D. 4

Answer: B